



US 20140222411A1

(19) **United States**(12) **Patent Application Publication**
Chrysanthakopoulos(10) **Pub. No.: US 2014/0222411 A1**(43) **Pub. Date: Aug. 7, 2014**(54) **CREATION AND USE OF VIRTUAL DEVICE
DRIVERS ON A SERIAL BUS****Publication Classification**(71) Applicant: **MICROSOFT CORPORATION,**
REDMOND, WA (US)(72) Inventor: **Georgios Chrysanthakopoulos,**
Kirkland, WA (US)(73) Assignee: **MICROSOFT CORPORATION,**
REDMOND, WA (US)(51) **Int. Cl.****G06F 9/44** (2006.01)**G06F 9/455** (2006.01)(52) **U.S. Cl.**CPC **G06F 9/4411** (2013.01); **G06F 9/455**
(2013.01)USPC **703/24**(21) Appl. No.: **14/250,735**(22) Filed: **Apr. 11, 2014****Related U.S. Application Data**

(63) Continuation of application No. 13/853,673, filed on Mar. 29, 2013, now Pat. No. 8,731,898, which is a continuation of application No. 12/711,633, filed on Feb. 24, 2010, now Pat. No. 8,412,508, which is a continuation of application No. 11/004,927, filed on Dec. 7, 2004, now Pat. No. 7,698,122, which is a continuation of application No. 09/559,531, filed on Apr. 28, 2000, now Pat. No. 6,968,307.

(57) **ABSTRACT**

A node on a serial bus, preferably a device such as a personal computer (PC), can emulate other devices using virtual device drivers. A PC connected to a 1394 bus exposes its CROM on the bus which presents an image to other nodes on the 1394 bus and describes the functional units supported by the node. The CROM can be changed dynamically by adding unit directories to the CROM detailing peripherals connected to the PC. The PC can then be enumerated as the connected device by other PCs on the bus. The PC can emulate or morph itself into any desired device or even multiple devices at the same time. The invention also allows a PC to create devices that don't yet exist on the bus. The invention allows a user to create virtual device objects with device properties to have just in case a user plugs the particular device in to the PC.

